



⑪ Publication number: **0 545 673 A1**

⑫

EUROPEAN PATENT APPLICATION

⑳ Application number: **92310975.5**

㉑ Int. Cl.⁵: **B01L 7/02, B01L 3/00, G01N 21/03**

㉒ Date of filing: **01.12.92**

㉓ Priority: **02.12.91 JP 341787/91**

㉔ Date of publication of application:
09.06.93 Bulletin 93/23

㉕ Designated Contracting States:
DE FR GB IT NL SE

㉖ Applicant: **SEIKAGAKU KOGYO KABUSHIKI KAISHA**
1-5, Nihonbashi-Honcho 2-chome, Chuo-ku Tokyo 103 (JP)


㉗ Inventor: **Hiroshi, Tamura**
6-13 Nakato 4-chome
Musashimurayama-shi, Tokyo 208 (JP)
Inventor: **Shigenori, Tanaka**
3-15 Ogawanishimachi 5-chome
Kodaira-shi, Tokyo 187 (JP)

㉘ Representative: **Warren, Keith Stanley et al**
BARON & WARREN 18 South End Kensington
London W8 5BU (GB)

㉙ **Photometer.**

㉚ The present invention is directed generally to maintaining a microplate (1) containing test samples in its wells at an even temperature for measuring biochemical or biological reactions, such as an enzyme reaction, accompanying changes in absorbance. Monochromatic light of various wave lengths, emitted by a light source (3), are transmitted through the test samples in the wells of the microplate (1) so as to measure the absorbance of the test samples. A metal plate (2) with good heat conductivity is in contact with the bottom of each well in the microplate (1) and a perforated board (7) is disposed in spaced relation above the microplate (1) at the starting position thereof. Within a chamber 9, warm air, heated by a heater (17), is blown onto the microplate (1) through the perforated board (7) and is circulated along the metal plate (2).

Fig. 1



EP 0 545 673 A1

BEST AVAILABLE COPY

The present invention relates to a photometer for use in measuring biochemical or biological reactions accompanying changes in absorbance, such as, enzyme reactions and the like, more specifically, to one for evenly heating the microplate, separately adding a test sample in wells and maintaining the temperature so that no temperature difference is present between wells.

As illustrated in Fig.4, a test sample 14 is added to each well 11 in a microplate comprising a lid part 15 made from a transparent synthetic resin and a wells part 12 made from a transparent synthetic resin and having a plurality of wells 11 inter-coupled with a plate member 10. The microplate is evenly heated to accelerate enzyme reaction and the like. Monochromatic light with various wave lengths is transmitted to the test sample 14 during or after a reaction to measure the absorbance of the test sample 14 in each well 11. Then, biochemical or biological measurements, such as, the enzyme activity or quantitative measurements of the substrate in the test sample 14, are carried out based on the measured absorbance.

In other words, as illustrated in Fig.6, a monochromatic light source 3 and a light detector 4 face each other. A microplate 1 containing the test sample 14 during or after reaction is placed on a carrier 5 and is transported between the light source 3 and the light detector 4. All test samples 14 in the wells 11 in the microplate 1 are scanned to measure absorbance and the absorbance values are related to the biochemical or biological reaction.

It is to be noted here that accurate and reproducible data cannot be obtained unless the absorbance measurements are carried out by maintaining the temperature of each test sample 14 in each well 11 in the microplate 1 even and constant. Otherwise the reaction temperature condition differs for each test sample 14 in each well 11.

To this end, temperature control means are proposed which use a fan to enforcedly circulate warmed air so that the microplate 1 is evenly heated and maintained at a constant temperature region without causing any temperature difference between wells.

However, in circulating warmed air within a chamber using a fan to stir air over the microplate 1, air flow on the surface of the microplate 1 partly differs; faster at the circumference and slower at the center portion.

This results in faster temperature rise at the circumference of the microplate 1 but slower at the center portion when the temperature of the microplate 1 in a chamber is to be raised by circulating the air. As a result, temperature difference between the test samples 14 in wells 11 in the microplate 1 is caused, thereby making it very difficult to obtain accurate and reproducible data due to uneven reaction temperature.

It is, therefore, an object of the present invention

to overcome the above mentioned problem. The present invention is directed to a photometer for transmitting monochromatic light with various wave lengths through test samples in a plurality of wells in a microplate for measuring the absorbance of the test samples and characterized in comprising a metal plate with good heat conductivity disposed substantially in contact with the bottom surface of each well in the microplate, a board having a plurality of openings therein and disposed with an air space over the microplate at the starting position thereof, air circulation means for enforcedly circulating air, and heating means to heat the air with all of the above constituents disposed in a chamber. Air is blown onto the upper surface of the microplate by way of the above-mentioned perforated board and is circulated along the metal plate with good heat conductivity.

In order that the invention may be more readily understood, reference will now be made to the accompanying drawings, in which:-

Fig.1 is a side view of one embodiment of photometer according to the present invention.

Fig.2 is a cross-section view of a part of the photometer in Fig.1.

Fig.3 is a plan view of an important part of the photometer in Fig.1.

Fig.4(a),(b) and (c) are a cross-section view of the lid part, a cross-section view of the wells part and a plan view of the wells part of the microplate to be used in the present and a conventional photometer, respectively.

Fig.5 is a plan view of an important part of another embodiment of the photometer in Fig.1.

Fig.6 is a side view of one example of a conventional photometer.

Illustrated in Fig.1 is an photometer according to the present invention. The said photometer comprises a carrier 5 on which is placed a microplate 1, a reciprocally driving unit (not shown) to repeatedly move the carrier 5 in the horizontal direction and absorbance measuring means (photometric unit) consisting of a light source 3 and a light detector 4 disposed facing each other at the upper and lower positions of the microplate 1 placed on the carrier 5 wherein all of the above constituents are disposed in a chamber 9.

The light source 3 in the absorbance measuring means comprises, as illustrated in detail in cross-section in Fig.2, a light bulb 31 a slit 32, a plurality of filters 33 for passing lights with different wave-lengths, and optical fibers 34 to split the monochromatic light selected by the filters 33 into a plurality of lights equal to the columns of wells 11 in the microplate 1. On the other hand, the light detector 4 comprises n number of photoelectric transducers 4, such as photo-transistors, disposed of the output ends of the optical fibers 34.

In order to enforcedly circulate the warmed air into the chamber 9, there are a heater 17, a fan 16 and

an partition 8 to form a flow path. Additionally, there is provided a sensor 18 of high sensitivity and high precision to detect the circulating air temperature. The output from the sensor is used to control the heater 17 so as to maintain the constant temperature.

The microplate 1 is placed on a perforated aluminum plate 2 with good heat conductivity as illustrated in cross-section and plan views in Fig.2 and 3, respectively. Openings 21 in the aluminum plate 2 correspond to the wells 11 in the microplate 1. The aluminum plate 2 is mounted on the carrier 5 by screws.

The perforated plate 2 with good heat conductivity is not limited only to aluminum but may be duralumin, stainless steel copper or the like. The size and shape of the plate may be selected to be adapted to the bottom of the microplate 1 so that the surface of the plate is substantially in contact with the bottom surface of the wells 11.

In other words as illustrated in Fig.4(b), there is provided a continuous pedestal portion 13 at the bottom periphery of the wells part 12 of the microplate 1. Since there is a little gap t between the bottom surface of the wells 11 and the bottom of the portion 13, the perforated plate 2 is preferably of size and shape so that the plate engages the inside of the continuous pedestal portion 13 and the upper surface of the plate comes in contact with the bottom of the well 11.

Additionally, there is provided a perforated synthetic resin board 7 disposed on the microplate 1 with an air space.

The fan 16 and the heater 17 are operated in advance to circulate warmed air within the chamber 9. Subsequently, the test sample 14 is added to each well 11 in the microplate 1 and the wells 11 are covered with the lid part 15. The microplate 1 is then placed on the carrier 5 in such a manner that the perforated aluminum plate 2 substantially comes in contact with the bottom of each well 11.

The driving unit is run to repeatedly reciprocate the carrier 5 in the horizontal direction. Each test sample 14 added to each well 11 in the microplate 1 is allowed to pass between the light source 3 and the light detector 4 to measure and record the absorbance changes of each test sample 14. It is to be noted here that the filter 33 is switched to select different monochromatic light according to the kind of the test sample 14 for measuring absorbance of the test sample.

A part of the air warmed by the heater 17 and circulated by the fan 16 during measurements is gently blown onto the upper surface of the microplate 1 by way of the perforated synthetic resin board 7. The other part of the warmed air flows between the bottom of perforated aluminum plate 2 under the bottom of the microplate 1 and the wall surface of the chamber 9.

As mentioned herein before, the warmed air is gently blown onto the entire upper surface of the mi-

croplate 1 by way of the perforated synthetic resin board 7, thereby evenly heating the upper surface. Also, the perforated aluminium plate 2 with good heat conductivity extends over the whole bottom of the microplate 1 thereby generally heating the bottom of the wells 11 all over the microplate.

Now, in the case of moving only the microplate 1 from the starting position to the measurement position and maintaining the plate 2 with good heat conductivity immovable, the plate 2 adapted to the bottom of the microplate 1 may not have openings 21. In this case, the good heat conductive plate 2 may be positioned at any suitable place for heating the microplate 1.

The number of wells (columns and rows) of the microplate 1 may be chosen from any desired value but is typically 96 (8x12).

Also, in manufacturing the microplate by injection molding, the microplate may have projections on the bottom due to molding die or mechanical strength. In this case, the perforated aluminum plate 2 with good heat conductivity may have cut-away portions 22 to receive the projections as illustrated in Fig.5.

As understood from the above description of the preferred embodiments, the photometer according to the present invention can maintain all of the test samples 14 added to the wells 11 in the microplate 1 at a uniform and accurate temperature, thereby constantly maintaining the reaction condition of each test sample required for accurate and reproducible data.

Claims

1. A photometer for transmitting monochromatic light of various wave lengths through test samples (14) in a plurality of wells (11) in a microplate (1) for measuring the absorbance of the test samples (14), characterised by a metal plate (2) having good heat conductivity for disposing substantially in contact with the bottom surface of each well (11) of the microplate (1), a board (7) having a plurality of openings therein for disposing in spaced relation over the microplate (1) at the starting position thereof, air circulation means (16) for circulating air, and heating means (17) for heating the air and the aforementioned components in a chamber (9) whereby air is blown onto the upper surface of the microplate (1) by way of the board (7) having openings therein and is circulated along the metal plate (2).
2. A photometer in accordance with claim 1, characterised in that the metal plate (2) is formed with openings (21) at locations corresponding to the wells (11) in the microplate (1) under which the metal plate (2) is adapted to be placed.

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5





Fig. 6





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 92 31 0975

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
A	DE-A-3 441 179 (DYNATECH DEUTSCHLAND) * the whole document *	1,2	B01L7/02 B01L3/00 G01N21/03
A	DE-A-3 204 578 (OLYMPUS OPTICAL KK) * the whole document *	1,2	
A	WO-A-8 700 281 (LAB-SYSTEMS OY) * the whole document *	1	
A	EP-A-0 339 824 (BARNSTEAD THERMOLYNE CORPORATION) * abstract; figures 5,7 *	1	
			TECHNICAL FIELDS SEARCHED (Int. Cl.5)
			B01L G01N
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 23 FEBRUARY 1993	Examiner SCHEU M.
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM L50 (3.82 (P0401))

THIS PAGE BLANK (USPTO)